

IMTEC TRED

WATER-BASED SINGLE-COMPONENT NON-SKID COATING

FEATURES

- Non flammable
- Versatile - can be used on most properly prepared surfaces
- Waterproof

RECOMMENDED USES

- To provide a non-skid surface
- To waterproof deck areas

SPECIFICATION DATA

POT LIFE:	Indefinite
FLASH POINT:	Nil
SOLVENT:	Water
GLOSS LEVEL:	Satin
STANDARD COLOURS:	White, Off-White, Light Grey
SPECIAL COLOURS:	Can be tinted to suit with water based tinters
APPLICATION METHOD:	Brush, Textured Roller
CLEAN-UP:	Tools and equipment may be cleaned up immediately
STORAGE:	Keep container tightly closed until just before use
THEORETICAL COVERAGE RATE:	Approximately 3m ² per litre per coat

SURFACE PREPARATION

Surface should be free of dust, oil and grease. If necessary, clean using Imtec C8765 Industrial Cleaner or similar.

STEEL/ALLOY

Abrade the surface using at least 120 grit paper and apply one coat of U-2554 High Build Primer at a coverage rate of four square metres per litre. Allow to cure then sand with 120-180 grit paper.

- Mask up areas to be coated.

TIMBER/GRP

Abrade the surface using 180 grit paper. Apply one coat of U2670 High Build Primer at the coverage rate of four square metres per litre. Allow to cure then sand using 120-180 grit paper.

- Mask up areas to be coated.

APPLICATION

IMTEC TRED is ready to use straight from the can but can be thinned sparingly with water if necessary. Pour enough material into a roller tray and apply the first coat using a suitable textured roller. The first coat should not be applied closer than 20mm to the tape. After 24 hours, apply a second coat, this time right up to the edge of the tape. After completing each section, remove the tape immediately and this will prevent the edge of the material lifting.

Note:

The amount of texture will depend on:

- 1 The type of textured roller used.
- 2 The amount of time left after initial application and prior to the first roll out of the material. The longer the period of time, the more textured the finish.

CLEANING

IMTEC TRED, being an acrylic, will stain and pick up dirt. However, this will generally be able to be cleaned using a good quality detergent such as Imtec C-8765 and a soft brush.

SCOMAR Distributors

A Division of Imtec Australia (1990) Pty Ltd

Brisbane Head Office & Warehouse

181 Boniface Street / PO Box 434

ARCHERFIELD QLD 4108

Ph: (07) 3277 9144

Fx: (07) 3875 1853

Email: info@scomar.com.au

Website: www.scomar.com.au

Sydney Office & Warehouse

30/176 South Creek Road / PO Box 5051

DEE WHY NSW 2099

Ph: (02) 9981 7444

Fx: (02) 9981 7477

Email: scomaraust@bigpond.com.au