

WERDOL STUNT OIL

WERDOL STUNT OIL

A single-component, specially formulated additive to suit WERDOL single-component varnishes (not suitable for WERDOL Aqua Marine Water-Based Interior Matte Varnish).

WERDOL Stunt Oil may be added to a WERDOL single-component varnish product, during brush application when longer wet-edge times are required, and/or when the brush starts to drag through the coating.

The addition of WERDOL stunt oil to the first coat of a WERDOL single-component varnish product when brushing, can also help promote adhesion to previously, heavily contaminated timber surfaces.

Generic type	A modified oil formulation.
Colour	Dark Amber Clear
Package	500ml / 1L
Flash point	nil
Recommended use	To extend wet-edge times while applying WERDOL single-component varnish products by brush application. May also be used in the first coat, to promote adhesion to previously, heavily contaminated timber surfaces.
Methods of application	Brush only

WERDOL STUNT OIL USAGE

EXTENDING THE WET-EDGE TIME

During brush application of a WERDOL single-component varnish product, wet-edge times may reduce due to any combination of factors such as high temperatures, humidity and time. This can cause the brush to “drag” or pull through the coating as it cures at a faster rate. If this starts to occur, add 10% WERDOL Stunt Oil to the unused, and unthinned WERDOL Varnish product being applied. This may be increased, if desired, to a maximum 30%.

PROMOTING ADHESION

When a previously heavily contaminated timber surface is to be coated, the addition of WERDOL Stunt Oil to the first coating of a WERDOL single-component varnish product will promote greater adhesion (during brush application only). Add 10% WERDOL Stunt Oil to the unused, and unthinned WERDOL Varnish product. This may be increased, if desired, to a maximum 30%.

WARNING: This scenario must not be performed in replacement of specific surface preparation steps, as detailed in all WERDOL Varnish product application guidelines.